(26H)

The Tibur series was inspired by Jerusalem stone, a well-known The Libur series was inspired by Jerusalem stone, a well-known limestone that has been used for centuries. This porcelain version has some special details that make it especially interesting. Even though it is a rectified tile, the edges are gently chiseled. The surface is also not completely flat; it has some undulation and some areas

of indentation to give the feel of old stone. The semi-polishing of the Vintage finish creates a unique effect on the undulated surface and has a soft "rubbed" feel to it. The mosaics - a Herringbone in the Vintage finish and the Intreccio Mosaic in the Natural finish - make this line a complete package.








Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

Colors



VWTRAD Aln

Size (Rectified) Natural Finish



VWTR-N/1224

VWTR-N/IM



VWTRSR

12 x 24



Vintage (Semi-Polished) Finish

Herringbone VWTR--V/HB

VWTR--V/1224

Product Information

Silver



Mosaics (Images not to scale)

Intereccio Mosaic Available in Natural Finish Only



Herringbone Mosaic

Available in Vintage Finish Only

Trim

12 x 24

Mosaics Intreccio

The surface bullnose is made from field tile that is cut, ground and re-glazed.

VWTR-N/SBN 3 x 24 Surface Bullnose Natural Finish VWTR-V/SBN 3 x 24 Surface Bullnose Vintage Finish

Usage & Installation Information

Tibur is suitable for residential to light and moderate commercial applications. To attain the proper mix of graphics and color it is important to pull from multiple boxes during installation, rotate pieces, and note the placement of the different images to get the proper final blend.

Most Italian manufacturers recommend a maximum offset of 8" (20cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles (ANSI A 108.2 Section 4.3.8). There are special setting requirements and materials for large format tiles. Please refer to the TCNA Handbook and guidelines by your mortar manufacturer for more information.

Non-Stock Sizes

Available in all colors. NON-STOCK SIZES and FINISHES are subject to minimum order quantities. Non-Stock prices are subject to change and should be reconfirmed at time of order. All sizes are Rectified.

Natural Fin	ral Finish - R11 C - 2 cm thick		R11 C - 2 cm thick
24 × 24	VWTRN/2424		
24 x 36	VWTRN/2436	24 x 36 Grip	VWTR-G/2436

Physical Characteristics (Natural Finish)

Physical Properties	Norms	Value
Water Absorption	10545-3	<0.5%
Frost Resistance	10545-12	Resistant
Slip Resistance	DIN51130	R10 / "B"
Dynamic Coefficient of Friction	DCOF	Wet ≥ 0.42

The Dynamic Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs. As noted in the American with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed.



