
MONOCIBEC
FABRILE GROUP

TRADITION



The cross-cut travertine look is more than traditional; it is perennially popular. Yet, as factories discontinue old travertine lines, it has become difficult to find replacements. With the Tradition series, we found one that will be a great option for customers seeking the travertine look. As a one color line, it manages to be far more than just one tile. The color has deep graphic detail and a nuanced blend of warm tones that make it a chameleon that moves from Ivory to Almond to Gold, depending on its surroundings. In fact, it will appeal to anyone who simply wants a beautiful stone-look in a warm color.



Travertine Beige (MOTNTB)

Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

Product Information

Color

Travertine Beige MOTNTB

Size (Rectified)

12 x 24 MOTNTB/1224
24 x 24 MOTNTB/2424

Mosaic

2 x 2 MOTNTB/22



2 x 2 Mosaic full sheet shown



Trim

The surface bullnose is made from field tile that is cut, ground and reglazed.

2 x 24 Surface Bullnose MOTNTB/SBN

Usage

Tradition is suitable for residential and moderate commercial use.

Installation

It is important to blend tile within each carton and from multiple cartons during installation, as well as changing the orientation of pieces with similar graphics to attain a proper mix.

Most Italian manufacturers recommend a maximum offset of 8" (20 cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles, ANSI A 108.2 section 4.3.8. Using a leveling system can improve the installation of this product.

Physical Properties

Physical Properties	Norms	Value
Flexion Resistance	10545-04	R ≥ 35 N/mm ² (average value)
Water Absorption	10545-03	≤ 0,05
Frost Resistance	10545-12	Resistant
PEI	10545-7	5
Slip Resistance	DIN 51130	R10
** Dynamic (DCOF) Coefficient of Friction	ANSI A 137.1	Wet ≥ 0.42

** These results are for the natural finish and for the normal productions; if there is concern about a particular production, it should be tested. The Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs.

As noted in the Americans with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed.

